LED Batten Light Manual


Application

Hotels, meeting rooms, offices, shopping malls, supermarkets, hospitals, schools, warehouse, passages, indoor parking lot and other need to be energy saving and high color rendering place.


Product main features

Made up of high quality led chips, constant current driver, excellent housing and high light transmittance PC cover. The batten light has a long life span, is very stable and reliable. Excellent housing is anodic oxidation after pure aluminum profiles processed. The luminaire shall never change colour and has excellent heat dissipation. No noise, no glare, lead-free, no mercury and other harmful substances. It is easy to install, with different installation methods such as surface mounted or suspension.


Item	0.3M	0.6M	0.9M	1.2M	1.5M	1.8M
Input Voltage	AC 220-240V	AC 220-240V	AC 220-240V	AC 220-240V	AC 220-240V	AC 220-240V
Rated Current	90mA	180mA	270mA	360mA	540mA	720mA
Frequency	50/60Hz					
Power	10W	20W	30W	40W	60W	80W
Color Temperature	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K
Luminous Flux	900lm	1800lm	2700lm	3600lm	5200lm	6600lm
CRI	Ra>80					
Dimension	L300*75*24mm	L600*75*24mm	L900 *75*24mm	L1200*75*24mm	L1500*75*24mm	L1800*75*24mm




A. Drill hole in desired position.



B. Screw the clip on the ceiling tightly



C. fasten the luminaire onto the clips.



D. Adjust the position of the fixture



