Installation and lamp change instructions for LEDF-SC-WW/WH.

Ensure the mains power is turned off and the product has cooled before working with this fitting. If you do not feel fully confident when dealing with electrical procedures, seek the advice of a qualified electrician.

Installation:

- 1. Turn off the mains power supply before starting the installation of this fitting.
- 2. Connect the driver to the 240V power supply, making sure that there is enough distance to reach the area the light fitting is be situated (sold separately).
- 3. There are 2 ways to fix these fittings to the surface. Firstly remove the LED unit from the fixing plate. To do this rotate the front of the fitting counter-clockwise and the two parts will come apart.




You can now either fix the fitting using the 2 screws provided or using the double sided sticky pad, also provided.

4. Make sure that the electrical wire is through the back of the fixing plate but not clipped into place. See the image below.



- 5. Position the fixing plate where you would like the fitting to be making sure that the wire from the fitting can connect into the connector block on the driver.
- 6. Using the screws provided, screw through the two holes in the fixing plate into the surface. Alternatively use the sticky pad. Peel off one side of the sticky pad and fix the back of the fixing plate. Peel off the second side and stick the fixing plate to the surface.



 Push the connector from the light fitting into the connection block on the driver. Repeat the above steps for any additional light fittings. Once complete turn the power back on.

