



## Mulu

### Mulu Self-Test IP65 LED emergency exit sign bulkhead, Black

Kosnic's LED Emergency Exit Sign or Emergency Bulkhead Luminaire is a self-contained, multi-purpose, nonmaintained or maintained\* 3-hour emergency exit sign or emergency luminaire solution. The fitting can be used with or without the emergency exit graphics. It is supplied with adaptable self-adhesive graphics that can be arranged to indicate escape routes as necessary.

**EESN0105S65/S-BLK ()**

## Specification

Voltage	220-240 Vac 50-60 Hz
Current (mA)	46
Rated Power (W)	5
CCT Words	Day Light
CCT (K)	6500
Total Luminous Flux (lm)	290 (maintained, no graphics), 110 (emergency, no graphics), 130 (maintained, with graphics), 50 (emergency, with graphics)
Beam Angle(°)	120
Nominal Lifetime (h)	30000
Power Factor	0.47
Ambient Temperature Range (°C)	0 to 40
Protection Rating	Class II
IP Rating	IP65
Battery Capacity	2600 mAh
Battery Charging Time	24 hours
Battery Code	KBAT2600LI1
Battery Life	4 years
Battery Type	Li-Ion
Battery Voltage	3.6V
Battery Warranty	4 Years
Emergency Operation Test	Self-Test (ATS Type S)
Emergency Conversion Time	1 second
Emergency Operating Time	3 hours
On-Site Warranty	2 Years

## Light Source Specification

Lumen Maintenance Factor (x.xx)	0.75
---------------------------------	------

## Technical Drawings

