


# GOLIATH Highbay LED Lighting



## Key Features:

- Super efficacy of 190lm/w
- Wattage Switchable
- CCT Switchable
- Optional Microwave Sensor
- IP66 / IK08 ratings
- Shatterproof Polycarbonate lens
- Lumileds LED Chips & Reflector system
- Sosen LED Driver
- 5 Years Warranty



Model Number	GOLIATH - I	GOLIATH-II
Input Voltage	100-277V 50/60Hz	100-277V 50/60Hz
Power	150w   120w   90w	215w   170w   130w
Lumen Output (lm)	28,500   22,800   17,100	40,850   33,300   24,700
Beam angle	120°	120°
Colour Temp (K)	3000K   4000K   5700K	3000K   4000K   5700K
Surge Protection	6Kv SPD	6Kv SPD
Efficacy (lm/W)	190lm/W	190lm/W
Housing Material	Black Die Cast Aluminium + Polycarbonate	
Mounting	Standard: Eyelet    Optional: Mounting bracket	
AC Cable	2m +	
Working Temp	-30°C to +45°C	
Protection	IP66   IK08 rated	
LED Lifetime @ 25°C	L80B10 > 50,000hrs   L70B10 > 100,000hrs	
Dimensions	∅ 300 x 111mm	∅ 350 x 112mm
Certifications:	UKCA, CE, RoHS	
Options:	Screw In Microwave Sensor, Mounting Bracket	



Frampton Roads  
Frampton, Boston  
PE20 1AY

01205 837104  
sales@dazzledlighting.co.uk  
www.dazzledlighting.co.uk

Lighting solutions for the 21<sup>st</sup> century