KITCHENIO 3-KIT | SURFACE DOWNLIGHT | WHITE **NOrdlux**®



Voltage (V): 230 Volt IP degree: IP20 Class (Class 1, Class 2, Class 3): Class 2 (Double isolated) Socket type: LED Module

Primary material: Plastic Secondary material: Plastic

Colour: White

Height (cm): 2.1

EAN: 5704924002816 TUN: 2113382 Item Number: 2015460101 Pcs Per Master Carton: 3 Sales Box Height (cm): 9

Sales Box Width(cm): 7 Sales Box Depth (cm): 11 Sales Box Volume m3: 0.0007 Product net weight (kg): 0.219

Brightness of light (Lumen): 170 Colour temperature (Kelvin): 3000/4000

Ra-value: 80 Lifetime (hours): 25000 Beam angle (°): 110 Candela (cd) (for directional

lamp only): 0 Energy class: G Actual watt (W): 2.2

• 2-step Moodmaker™ (3000/4000 kelvin) by your regular wall switch • Parallel connection possible • Recessed and surface mounting possible • Cable included (60 cm) • 5-year LED guarantee

The under-cabinet light Kitchenio is very flexible when it comes to installation as it can easily be recessed, or surface mounted using either screws or double tape. Especially, the included 2 or 4 wire connector block make Kitchenio ready for immediate installation. Equipped with both a 2-step Moodmaker™ and a memory and reset function enables you to change and save your

The 2-step Moodmaker™ within the Kitchenio under cabinet light enables the possibility to obtain warm light by one single click and cold light by another click on the switch.

