EMERGENCY CONVERSION KIT 2.5W 20-90VDC 3HR WITH REMOTE LED INDICATOR SELF TEST

ILEMPK012



Details

Quick Order Code: Barcode: Category: Range Name: Product Type: Product Body Finish: Market Segment: Finish: Warranty (Years): CE RoHS:

Physical Data

Product Length (mm): Product Depth (mm): Product Width (mm): Product Weight (g): Material: Construction: Bulb or Luminaire Shape: Luminaire Fixing: Placement / Application:

Electrical Data

Power Consumption (W) : Input Voltage (V): Output Voltage (V): Battery Configuration: Dimming: Driver Included: Electric Current: Emergency Type:

- 150122 5055788288879 Emergency Conversion Kit Emergency Conversion Kit Matt white. End cap blue Commercial indoor Matt white. End cap blue 3 Yes
- 240 28 50 220 Polycarbonate Injection moulding Rectangle In Ceiling Indoor, Emergency Lighting
- 2.5 220-240 20-90 LiFePo4 Non-Dimmable Yes AC Non-Maintained

Light Data

Frequency Range (Hz):	50/60

Environment

CE RoHS:	Yes
IK Rating (Impact Protection):	IK04
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	5
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	250
Package Length (mm):	28
Package Width (mm):	240
Package Depth (mm):	50

Portal.integral-led.com