

# LL T5 Electronic wall/cabinet Lights

## Installation Instructions

**SAFETY:** Suitable for indoor installations  
Before starting any electrical work always switch off at the mains  
if in any doubt, consult a qualified electrician

### IMPORTANT

This product is double insulated, **DO NOT** earth.

Fixing holes must be clear of obstructions (e.g. cables etc.).

Position the fitting so that the minimum distance between the lamp and any adjacent surface is 10mm.

The mains supply should be fused at 3 Amps.


Fittings may be butt-linked (Fig. 1) or lead-linked (Fig. 2) with the supplied lead or with a longer link lead (available separately).

Linkable up to 10 units.

Fig 1



Fig 2



### INSTRUCTIONS

- Select the appropriate brackets & screws for the mounting surface (Fig. 3).
- Use the fittings as a template to determine the desired spacing between the brackets (Fig. 4).
- Clip the fitting(s) to the brackets (Fig. 5) and link if required.
- Plug the mains cable to a fixed socket incorporating a 3 Amp fuse.

**WARNING: NOT SUITABLE FOR USE EXTERNALLY OR IN BATHROOMS**

Fig 3



Fig 4



### LAMP REPLACEMENT (Fig. 6)

- Turn off mains supply.
- Unclip plastic diffuser.
- Turn the lamp through 180 counter clockwise.
- Remove lamp.
- Insert new lamp & turn through 90 clockwise.
- Re-fit diffuser & reconnect the mains supply.




Fig 6

